

Behringer B2030A Specs

Low Frequency Driver	6.75" Polypropylene Diaphragm
Mid Frequency Driver	No
High Frequency Driver	.75" Ferro-Fuid Cooled Dome
LF Amplifier	75 Watts
HF Amplifier	35 Watts
Crossover	Active, 4th Order Linkwitz-Riley, 2kHz Frequency
Frequency Range	50 Hz - 21 kHz
Impedance	10 kOhms
Maximum Sound Pressure Level (SPL)	113 dB SPL @ 1 m
Controls and Indicators	Front: 1 x Power On LED 1 x Limiter Activated LED Rear: 1 x Power Switch 1 x Input Sensitivity Trim 1 x 4-Position LF Response Switch 1 x 4-Position LF Room Compensation Switch 1 x 4-Position HF Response Switch 1 x 3-Position Power Mode Switch

1 x 2-Position Mute Low Speaker Switch
1 x 2-Position Mute High Speaker Switch

Connectors 1 x XLR Female, Balanced
1 x 1/4" TRS Phone, Balanced

Shielded Yes

Dimensions (HxWxD) 12.5 x 8.4 x 8.3" (317 x 214 x 211mm)

Weight 21.6 lb (9.8 kg)

Specialties Magnetically Shielded
Front-Ported Bass Reflex Cabinet

Packaging Info

Package Weight 23 lb

Box Dimensions (LxWxH) 15 x 12.5 x 11"
