

PRODUCT-DETAILS

UPS PowerValue 11/31 T 20kVA

UPS PowerValue 11/31 T 20kVA



General Information

Extended Product Type	UPS PowerValue 11/31 T 20kVA
Product ID	4NWP100118R0001
ABB Type Designation	UPS PowerValue 11/31 T 20kVA
EAN	7640169260438
Catalog Description	UPS PowerValue 11/31 T 20kVA
Long Description	VFI UPS PowerValue 11/31 T 20000VA/18000W; 230V; 50/60Hz; 0 min

Additional Information

ABB Type Designation	UPS PowerValue 11/31 T 20kVA
Apparent Power Output	20000 V-A
CN8	85044000
Communication Interface	USB, RS-229
Communication Protocol and Connection	SNMP
Connection Type	Fixed Connection
Country of Origin	China (CN)
Customs Tariff Number	85044000
Data Sheet, Technical Information	4NWD002980
Declaration of Conformity - CE	4NWD00341
EAN	7640169260438
ETIM 6	EC000382 - UPS

ETIM 7	EC000382 - UPS
Efficiency	Overall 93.10 % Economy Mode (Eco-Mode) 97.00 %
Environmental Information	No declaration needed
Harmonic Distortion	2.00 %
Input Voltage (U _{in})	220 V 230 V 240 V 380 V 400 V 415 V
Input Voltage Type	AC
Instructions and Manuals	4NWD003235
Invoice Description	UPS PowerValue 11/31 T 20kVA
Made To Order	No
Minimum Order Quantity	1 piece
Number of Outputs	Fixed Connections 1
Number of Phases	Primary - 1 Primary - 3 Secondary - 1
Object Classification Code	G
Options Provided	Auto shut down function Potential free switch contact Network-management
Order Multiple	1 piece
Output Voltage (U _{out})	208 V 220 V 230 V 240 V
Package Level 1 Depth / Length	815 mm
Package Level 1 EAN	7640169260438
Package Level 1 Gross Weight	83 kg
Package Level 1 Height	1120 mm
Package Level 1 Units	1 piece
Package Level 1 Width	475 mm
Power Factor	0.9
Product Main Type	PowerValue 11/31 T
Product Name	UPS
Product Net Depth / Length	715 mm
Product Net Height	890 mm
Product Net Weight	67 kg
Product Net Width	350 mm
Quote Only	No
Rated Frequency (f)	Primary 50 Hz Primary 60 Hz Secondary 50 Hz Secondary 60 Hz
Rated Output Power	18000 W
RoHS Date	0516
RoHS Information	4NWD00341
RoHS Status	Following EU Directive 2011/65/EU
Selling Unit of Measure	piece
Uninterruptible Power Supply Form Factor	Tower
Uninterruptible Power Supply Topology	On-Line Double Conversion
WEEE B2C / B2B	Business To Business

WEEE Category

4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

UPS, Power Conditioning and Power Distribution → UPS → Single-Phase UPS → PowerValue 11/31 T IEC 230V

