

PRODUCT-DETAILS

UPS PowerValue 11T G2 2 kVA B

UPS PowerValue 11 T G2 2 kVA B



Información General

Extended Product Type	UPS PowerValue 11T G2 2 kVA B
Product ID	4NWP100161R0001
EAN	7640169261909
Catalog Description	UPS PowerValue 11 T G2 2 kVA B
Long Description	VFI online double conversion;1800W;9min;RS232;USB;mini COM slot

Información adicional

Apparent Power Output	2000 V·A
Battery Chemical Composition	Lead-Acid
Battery Runtime	5.5 minute [unit of time]
Battery Type	Portable
Battery Weight	2.5 kg
CN8	85044000
Communication Interface	USB, RS-232
Communication Protocol and Connection	SNMP
Connection Type	IEC C14
Country of Origin	China (CN)
Customs Tariff Number	85044000
Data Sheet, Technical Information	4NWD003883
Declaration of	4NWD003869

Conformity - CE	
E-Number (Finland)	8408611
E-Number (Sweden)	5257247
EAN	7640169261909
ETIM 6	EC000382 - UPS
ETIM 7	EC000382 - UPS
Efficiency	Overall 91.00 % Economy Mode (Eco-Mode) 98.00 %
Environmental Information	No declaration needed
Harmonic Distortion	5.00 %
Input Voltage (U _{in})	220 V 230 V 240 V
Input Voltage Type	AC
Instructions and Manuals	4NWD003883
Invoice Description	UPS PowerValue 11 T G2 2 kVA B
Minimum Order Quantity	1 piece
Number of Batteries	4
Number of Outputs	C13 Connection 4
Number of Phases	Primary - 1 Secondary - 1
Object Classification Code	G
Options Provided	Auto shut down function Potential free switch contact Network-management
Output Voltage (U _{out})	208 V 220 V 230 V 240 V
Package Level 1 Depth / Length	500 mm
Package Level 1 EAN	7640169261909
Package Level 1 Gross Weight	19.6 kg
Package Level 1 Height	464 mm
Package Level 1 Units	1 piece
Package Level 1 Width	324 mm
Power Factor	0.9
Product Main Type	PowerValue 11T G2
Product Name	UPS
Product Net Depth / Length	399 mm
Product Net Height	327 mm
Product Net Weight	17.2 kg
Product Net Width	190 mm
Rated Frequency (f)	Primary 50 Hz Primary 60 Hz Secondary 50 Hz Secondary 60 Hz
Rated Output Power	1800 W
RoHS Date	0318
RoHS Information	4NWD003869
RoHS Status	Following EU Directive 2011/65/EU
Selling Unit of Measure	piece
Uninterruptible Power Supply Form Factor	Tower
Uninterruptible Power Supply Topology	On-Line Double Conversion
WEEE B2C / B2B	Business To Business

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Categorías

SAI y acondicionador de energía → SAI → Sistemas monofásicos independientes → PowerValue 11 T G2 IEC 230V

