



SMT1000IC

RoHS

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other ...

Includes: Cat 5 Ethernet cable, Installation guide, USB cable

Technical Specifications

Output

Max Configurable Power (Watts)	700 Watts / 1.0kVA
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220, 240
Topology	Line interactive
Waveform type	Sine wave
Transfer Time	6 ms typical : 10 ms maximum

Input

Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input voltage range for main operations	151 - 302 Adjustable, 160 - 286V
Other Input Voltages	220, 240

Batteries & Runtime

Battery type	Lead-acid battery
Typical recharge time	3hour(s)
Replacement Battery	RBC6
Expected Battery Life (years)	3 - 5

RBC Quantity	1
Battery Charge Power (Watts)	88 Watts
Runtime	View Runtime Graph View Runtime Chart
Efficiency	View Efficiency Graph

Communications & Management

Interface Port(s)	SmartSlot, USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	Optional
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering

Surge energy rating	459Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	219MM, 21.9CM
Maximum Width	171MM, 17.1CM
Maximum Depth	439MM, 43.9CM
Net Weight	19.4KG
Shipping weight	22.77KG
Shipping Height	376MM, 37.6CM
Shipping Width	328MM, 32.8CM
Shipping Depth	595MM, 59.5CM
Color	Black
Units per Pallet	12.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	41.0dBA
Online thermal dissipation	100.0BTU/hr

Conformance

Approvals	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE
------------------	---

Standard warranty

3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status

RoHS

Compliant

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our [Privacy Policy](#).

Email

I am a...

Sign up

WHO WE ARE

[About APC](#)

[Investor Relations](#)

[Careers](#)

[Sustainability](#)

CONNECT WITH US

[Press](#)

[APC Blog](#)

[Schneider Electric Data Centre Blog](#)

[Contact Us](#)

FIND A RESELLER

Zip/Postal Code

Find

CATALOG KEYCODE

Enter Key Code

Go



[Terms & Conditions](#)

[Data Privacy and Cookie Policy](#)

2021, APC by Schneider Electric