



## SMT750IC

RoHS

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other ...

Includes: USB cable



## Technical Specifications

### Output

Max Configurable Power (Watts)	500 Watts / 750VA
Output Voltage Distortion	Less than 5 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220, 240
Topology	Line interactive
Waveform type	Sine wave
Transfer Time	6 ms typical : 10 ms maximum

### Input

Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input voltage range for main operations	151 - 302 Adjustable, 160 - 280V
Number of Power Cords	1
Other Input Voltages	220, 240

### Batteries & Runtime

Battery type	Lead-acid battery
Typical recharge time	3hour(s)
Replacement Battery	<a href="#">RBC48</a>
Expected Battery Life (years)	3 - 5

<b>RBC Quantity</b>	1
<b>Battery Charge Power (Watts)</b>	49 Watts
<b>Runtime</b>	<a href="#">View Runtime Graph</a> <a href="#">View Runtime Chart</a>
<b>Efficiency</b>	<a href="#">View Efficiency Graph</a>

## Communications & Management

<b>Interface Port(s)</b>	SmartSlot, USB
<b>Control panel</b>	Multifunction LCD status and control console
<b>Audible Alarm</b>	Alarm when on battery : distinctive low battery alarm : configurable delays
<b>Emergency Power Off (EPO)</b>	Optional
<b>Available SmartSlot™ Interface Quantity</b>	1

## Surge Protection and Filtering

<b>Surge energy rating</b>	540Joules
<b>Filtering</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Physical

<b>Maximum Height</b>	161MM, 16.1CM
<b>Maximum Width</b>	138MM, 13.8CM
<b>Maximum Depth</b>	369MM, 36.9CM
<b>Net Weight</b>	11.8KG
<b>Shipping weight</b>	14.23KG
<b>Shipping Height</b>	301MM, 30.1CM
<b>Shipping Width</b>	278MM, 27.8CM
<b>Shipping Depth</b>	499MM, 49.9CM
<b>Color</b>	Black
<b>Units per Pallet</b>	24.0

## Environmental

<b>Operating Temperature</b>	0 - 40 °C
<b>Operating Relative Humidity</b>	0 - 95 %
<b>Operating Elevation</b>	0 - 3048meters
<b>Storage Temperature</b>	-15 - 45 °C
<b>Storage Relative Humidity</b>	0 - 95 %
<b>Storage Elevation</b>	0 - 15240meters
<b>Audible noise at 1 meter from surface of unit</b>	40.0dBA
<b>Online thermal dissipation</b>	90.0BTU/hr

## Conformance

<b>Approvals</b>	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE
------------------	---

**Standard warranty**

3 years repair or replace (excluding battery) and 2 years for battery

---

**Sustainable Offer Status**

**RoHS**

Compliant

---

**SIGN UP FOR EMAIL**

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our [Privacy Policy](#).

Email

I am a...

Sign up

**WHO WE ARE**

[About APC](#)

[Investor Relations](#)

[Careers](#)

[Sustainability](#)

**CONNECT WITH US**

[Press](#)

[APC Blog](#)

[Schneider Electric Data Centre Blog](#)

[Contact Us](#)

**FIND A RESELLER**

Zip/Postal Code

Find

**CATALOG KEYCODE**

Enter Key Code

Go



[Terms & Conditions](#)

[Data Privacy and Cookie Policy](#)

2021, APC by Schneider Electric