

PRODUCT SPECIFICATION

Vertiv Liebert GXT5 10 KVA / 10 kW 230V Rack/Tower UPS Specifications

Manu. Code	GXT5-10KIRT5UXLE
Weight (approx)	74500.00g
Product Type	UPS
Technical details	
Brand	Vertiv
Collection	
Collection Model	Vertiv GXT5 10 KVA / 10 kW 230V Rack/Tower UPS
Design	
Product colour	Black
Form Factor	Rackmount/Tower
Cooling type	Active
Display	LCD
Safety	IEC62040-1:2008
Ports & interfaces	
USB port	Y
AC outlet types	C13 coupler,C19 coupler,IEC 320,Terminal C13 coupler, C19 coupler, IEC 320, Terminal
Power plug	Terminal
AC outlets quantity	8 AC outlet(s)
RS-232 ports	1
Serial ports quantity	1
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery Capacity	9 Ah
Battery voltage	12 V
Typical backup time at full load	2 min
Typical backup time at half load	7 min
Battery recharge time(90%)	5 h
Battery recharge time (90%)	5 h
Hot-swap battery	Y
	1

**Power
Power factor**

Weight & dimensions

Width 430 mm

Depth 630 mm

Height 217 mm

Weight 74.5 kg

Performance

**International
Protection (IP) code** IP20

Features

UPS topology Double-conversion (Online)

Output power capacity 10000 VA

Output power 10000 W

Waveform Pure sine

**Input operation voltage
(min)** 176 V

**Input operation voltage
(max)** 288 V

Input frequency 50/60 Hz

**Output operation
voltage (min)** 230 V

**Output operation
voltage (max)** 240 V

Output frequency 50/60 Hz

**Output voltage
regulation** 3%

Number of input phases 1

**Number of output
phases** 1

**Single-phase input
voltage supported** 220,230,240 V

Efficiency 95%

**Efficiency (On-line
mode)** 95%

Input power factor 0.99

Output power factor 1

**Emergency Power Off
(EPO)** Y

**Overload capacity (5
minute)** 125%

Overload capacity (1 minute)	150%
Power protection features	Overload
Rack capacity	5U
Audible alarm(s)	Y
Noise level	55 dB
Output Voltage	230 V
Operational conditions	
Operating relative humidity (H-H)	0 - 95%
Operating temperature (T-T)	0 - 40 C
Storage temperature (T-T)	-15 - 40 C
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Certificates	
Certification	CE, EMI/EMC/C-Tick EMC, ESD
RoHS compliance	Y
Technical details	
Sustainability certificates	RoHS
Packaging data	
Battery Type	VRLA
Number of Batteries Supported	16
Package height	520 mm
Package width	646 mm
Package depth	816 mm
Package weight	93 kg
MPN	GXT5-10KIRT5UXLE