


**MODEL : NV 150-12**



**Plane Chart:**

Unit:(mm) Terminal type:(T3)


**ISO 9001**  
**ISO 14001**  
**OHSAS18001**
**Parameter Chart:**


VOLTS		12V
Capacity(25°C)	10 hours rate (15A)	150Ah
Discharge Current Testing (25°C)	1 hours rate (82.5A)	83Ah
	3 hours rate (37.5A)	113Ah
Internal Resistance	Full Charged Battery 25°C	3.4mΩ
Capacity Affected By Temperature	40°C	104%
	25°C	100%
	0°C	83%
	-15°C	65%
Residual Capacity (25°C)	Capacity After 3 Months Storage	91%
	Capacity After 6 Months Storage	82%
	Capacity After 12 Months Storage	65%
Charge (Constant Voltage)	Cycle (25°C)	Initial Charging Current Less Than 45A Voltage 14.5~14.9V
	Float (25°C)	Charge Voltage 13.6~13.8V
Weight (Approx)		42.5Kg

★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.


**Residual Capacity**

**Discharge Current 25°C**


**MODEL : NV 150-12**

**Constant voltage charging characteristics**



**Float Life**



**Constant Current Discharge Characteristics(A,25°C)**

F.V/Time	15min	30min	60min	2h	3h	4h	5h	8h	10h	20h
9.60V	267.3	158.4	96.5	54.3	39.2	31.1	27.3	18.1	15.2	7.8
10.2V	256.4	152.5	92.7	53.5	38.6	30.7	26.9	17.9	15.1	7.8
10.5V	251.5	148.5	90.8	53.0	38.2	30.5	26.6	17.8	15.0	7.8
10.8V	243.5	144.5	88.0	52.4	37.8	29.5	26.4	17.8	15.0	7.7

**Constant Power Discharge Characteristic(Watt,25°C)**

F.V/Time	15min	30min	60min	2h	3h	4h	5h	8h	10h	20h
9.60V	2935.4	1777.1	1100.9	628.7	461.3	365.3	322.7	214.8	181.2	93.9
10.2V	2815.6	1710.7	1056.3	618.8	454.4	360.4	318.8	212.9	179.2	93.9
10.5V	2760.1	1666.2	1034.6	612.8	449.5	358.4	314.8	211.9	178.2	93.2
10.8V	2674.0	1621.6	1002.9	606.9	445.5	347.5	312.8	210.9	177.2	92.7

**Capacity Factors With Different Temperature**

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
GEL Battery	12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%

★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.