

Specification

Eaton 9SX 9SX6KIRT - UPS - 5400 Watt - 6000 VA

Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Rack Size	19" - 3U
Weight	48 kg
Input Voltage	AC 200/208/220/230/240 V
Output Voltage	AC 200/208/220/230/240 V \pm 1%
Power Capacity	5400 Watt / 6000 VA
Input Connectors	Hardwire
Output connectors	8 x power IEC 60320 C13 2 x power IEC 60320 C19 1 x hardwire
Battery Form Factor	Plug-in module
Run Time (Up To)	3 min at full load
Networking	RS-232, USB
Included Accessories	Tower stand
Dimensions (WxDxH)	44 cm x 68.5 cm x 13 cm
Environmental Standards	ENERGY STAR
Manufacturer Warranty	2-year warranty

Extended Specification

General

Battery Enclosure Type	Plug-in module
Device Type	UPS - Power Factor Correction (PFC) - rack-mountable / external
Height (Rack Units)	3U
Rack Size	19"

Battery

Voltage Provided	12 V
------------------	------

Dimensions & Weight

Depth	68.5 cm
Height	13 cm
Weight	48 kg
Width	44 cm

Environmental Parameters

Max Operating Temperature	40 °C
Min Operating Temperature	0 °C
Sound Emission	45 dB

Environmental Standards

ENERGY STAR	Yes
-------------	-----

Expansion / Connectivity

Expansion Slots	1 (total) / 1 (free) x Expansion Slot
Interfaces	1 x RS-232 - 9 pin D-Sub (DB-9) 1 x USB - 4 pin USB Type B 1 x EPO (emergency power off)

Manufacturer Warranty

Service & Support	Limited warranty - 2 years
-------------------	----------------------------

Miscellaneous

Cables Included	2 x power cable - external Serial cable - external USB cable - external
-----------------	---

Compliant Standards	UL, CISPR 22 Class A, ISO 9001, ISO 140001, IEC 61000-3-2, IEC 61000-3-3, IEC 61000-4-11, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, UL 1778, CB, IEC 62040-3, IEC 62040-1-1, IEC 62040-2, FCC Part 15 A, CSA 22.2, IEC 61000-2-2, EN 62040-1-1, EN 62040-2
---------------------	--

Features	Advance Battery Management (ABM), LCD display, LED indicators, deep discharge protection, cold-start function, automatic self-test
----------	--

Included Accessories	Tower stand
----------------------	-------------

Rack Mounting Kit	Included
-------------------	----------

Networking

Remote Management Interface	RS-232, USB
-----------------------------	-------------

Power Device

Circuit Protection	Fuse
Frequency Provided	50/60 Hz
Frequency Required	40 - 70 Hz
Input Connectors	Hardwire
Input Voltage	AC 200/208/220/230/240 V
Input Voltage Range	AC 176 - 276 V
Max Electric Current	25.2 A

Power Device

Output Voltage AC 200/208/220/230/240 V \pm 1% - 50/60 Hz

Output Waveform Sinewave

Power Capacity 5400 Watt / 6000 VA

Power Output Connectors Details 8 x power IEC 60320 C13 | 2 x power IEC 60320 C19 | 1 x hardwire

Surge Suppression Yes

UPS Technology On-line

Software / System Requirements

Software Included Intelligent Power Software Suite