

Output

Nominal Output Voltage

208V, 230V

Maximum Total Current Draw

16

Output Connections

(12) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage

200V, 208V, 230V

Input frequency

50/60 Hz

Input Connections

IEC-320 C20

Cord Length

8.2ft (2.5meters)

Number of Power Cords

1

Load Capacity

3680VA

Maximum Input Current

16A

Physical

Maximum Height

1.75inches (44MM, 4.4CM)

Maximum Width

17.6inches (447MM, 44.7CM)

Maximum Depth

2.25inches (57MM, 5.7CM)

Rack Height

1U

Net Weight

4.5lbs. (2.05KG)

Shipping weight

8.0lbs. (3.64KG)

Shipping Height

2.75inches (70MM, 7.0CM)

Shipping Width

18.25inches (464MM, 46.4CM)

Shipping Depth

9.0inches (229MM, 22.9CM)

Color

Environmental

Operating Temperature

32 – 113 °F (0 – 45 °C)

Operating Relative Humidity

0 – 95 %

Operating Elevation

0–10000ft (0–3000meters)

Storage Temperature

–25 – 65 °C

Storage Relative Humidity

0 – 95 %

Storage Elevation

0–50000ft (0–15000meters)

Conformance

Approvals

cUL Listed, CE, Queensland Australia, UL 60950, UL Listed, VDE

Standard warranty

2 years repair or replace

Sustainable Offer Status

RoHS

Compliant

REACH

REACH: Contains No SVHCs

PEP

Available in Documentation tab

EOL

Available in Documentation tab

Other Environmental Compliance

China RoHS

Proposition 65 Warning

Available in Documentation tab