

Detailed Tech Specification

Output

- Nominal Output Voltage
208V , 230V
- Maximum Total Current Draw
16
- Output Connections
(8) IEC 320 C13 (Battery Backup)

Input

- Nominal Input Voltage
200V , 208V , 230V
- Input frequency
50/60 Hz
- Input Connections
IEC-320 C20
- Cord Length
2.5meters
- Acceptable Input Voltage
200-240VAC
- Number of Power Cords
1
- Load Capacity
3680VA
- Maximum Input Current
20A
- Regulatory Derated Input Current (North America)
16A

Physical

- Maximum Height
44mm , 4.4CM
- Maximum Width
445mm , 44.5CM
- Maximum Depth
108mm , 10.8CM

- Rack Height
1U
- Net Weight
2.27KG
- Shipping weight
3.45KG
- Shipping Height
70mm , 7.0CM
- Shipping Width
470mm , 47.0CM
- Shipping Depth
343mm , 34.3CM
- Color
Black

Environmental

- Operating Temperature
0 – 45 °C
- Operating Relative Humidity
0 – 95 %
- Operating Elevation
0-3000meters
- Storage Temperature
-25 – 65 °C
- Storage Relative Humidity
0 – 95 %
- Storage Elevation
0-15000meters

Conformance

- Approvals
cUL Listed, CE, CSA, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, GOST, IRAM, MIC, UL 60950, UL Listed, VDE, VCCI
- Standard warranty
2 years repair or replace

Sustainable Offer Status

- RoHS
Compliant
- REACH

REACH: Contains No SVHCs

- Battery Directive
Compliant
- Battery Notes
ts_Battery_Notes